



6N135.6N136.JOC4502.JOC4503 Series

1Mbit/s High Speed Transistor Photo Coupler

Description

The 6N135, 6N136, JOC450X series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a silicon high speed photo transistor in a plastic DIP8 package with different lead forming options.

A separate design between photodiode and transistor reduces the base-collector capacitance of the input transistor which improves the speed by several orders of magnitude over conventional phototransistor optocouplers.


Features

- High isolation 5000 VRMS
- DC input with transistor output
- Operating temperature range - 55 °C to 100 °C
- REACH compliance
- Halogen free (Optional)
- MSL class 1
- Regulatory Approvals
 - UL
 - VDE

Applications

- Line receivers
- Telecommunication equipment
- Out interface to CMOS-LSTTL-TTL
- Wide bandwidth analog coupling
- Pulse transformer replacement
- Computer-peripheral interface


SCHEMATIC



PIN DEFINITION

| | |
|------------------|--|
| 1.NC | 8.VCC |
| 2.Anode | 7.VB(for 6N135/6N136) NC(for JOC4502/JOC4503) |
| 3.Cathode | 6.VO |
| 4.NC | 5.GND |

OUTLINE



ABSOLUTE MAXIMUM RATINGS

| PARAMETER | SYMBOL | VALUE | UNIT | Note |
|------------------------------|----------------|---------|------------------|------|
| INPUT | | | | |
| Forward Current | I_F | 25 | mA | |
| Peak Forward Current | I_{FP} | 50 | mA | 1 |
| Peak Transient Current | $I_{F(trans)}$ | 1 | A | 2 |
| Reverse Voltage | V_R | 5 | V | |
| Input Power Dissipation | P_I | 100 | mW | |
| OUTPUT | | | | |
| Supply Voltage | V_{CC} | -0.5~30 | V | |
| Output Voltage | V_O | -0.5~20 | V | |
| Output Current | I_O | 50 | mA | |
| Emitter-Base Reverse Voltage | V_{EBR} | 5 | V | |
| Base Current | I_B | 5 | mA | |
| Output Power Dissipation | P_O | 100 | mW | |
| COMMON | | | | |
| Total Power Dissipation | P_{tot} | 200 | mW | |
| Isolation Voltage | V_{iso} | 5000 | V _{rms} | 3 |
| Operating Temperature | T_{opr} | -55~100 | °C | |
| Storage Temperature | T_{stg} | -55~150 | °C | |
| Soldering Temperature | T_{sol} | 260 | °C | 4 |

Note 1. 50% duty, 1ms P.W

Note 2. $\leq 1\mu s$ P.W,300pps

Note 3. AC For 1 Minute, R.H. = 40 ~ 60%

Note 4. For 10 seconds

ELECTRICAL OPTICAL CHARACTERISTICS

| PARAMETER | SYMBOL | MIN | TYP | MAX | UNIT | TEST CONDITION | NOTE |
|--|-----------|-----|-------|-----|---------------|--|------|
| INPUT(at Ta=0 to 70°C , unless specified otherwise) | | | | | | | |
| Forward Voltage | V_F | - | 1.45 | 1.8 | V | $I_F=16\text{mA}$ | |
| Reverse Current | I_R | - | - | 10 | μA | $V_R=5\text{V}$ | |
| Input Capacitance | C_{in} | - | 60 | - | pF | $V=0, f=1\text{MHz}$ | |
| OUTPUT(at Ta=0 to 70°C , unless specified otherwise) | | | | | | | |
| High Level Supply Current | I_{CCH} | - | 0.01 | 1 | μA | $I_F=0\text{mA}, V_O=\text{Open}, V_{CC}=15\text{V}, T_a=25^\circ\text{C}$ | |
| | | - | - | 2 | μA | $I_F=0\text{mA}, V_O=\text{Open}, V_{CC}=15\text{V}$ | |
| Low Level Supply Current | I_{CCL} | - | 200 | - | μA | $I_F=16\text{mA}, V_O=\text{Open}, V_{CC}=15\text{V}$ | |
| Logic High Output Current | I_{OH} | - | 0.001 | 0.5 | μA | $I_F=0\text{mA}, V_O=V_{CC}=5.5\text{V}, T_a=25^\circ\text{C}$ | |
| | | - | 0.01 | 1 | μA | $I_F=0\text{mA}, V_O=V_{CC}=15\text{V}, T_a=25^\circ\text{C}$ | |
| | | - | - | 50 | μA | $I_F=0\text{mA}, V_O=V_{CC}=15\text{V}$ | |

ELECTRICAL OPTICAL CHARACTERISTICS

| PARAMETER | SYMBOL | MIN | TYP | MAX | UNIT | TEST CONDITION | NOTE | |
|--|----------|-----------|-----------|--|----------|--|------|---|
| TRANSFER CHARACTERISTICS(at Ta=0 to 70°C , unless specified otherwise) | | | | | | | | |
| Current Transfer Ratio | 6N135 | CTR | 7 | - | 50 | $I_F = 16\text{mA}$, $V_O = 0.4\text{V}$, $V_{CC}=4.5\text{V}$, $T_a=25^\circ\text{C}$ | | |
| | 6N136 | | 19 | - | 50 | | | |
| | JOC4502 | | | | | | | |
| | JOC4503 | | | | | | | |
| | 6N135 | | 5 | - | - | | | $I_F = 16\text{mA}$, $V_O = 0.5\text{V}$, $V_{CC}=4.5\text{V}$ |
| 6N136 | 15 | - | - | | | | | |
| JOC4502 | | | | | | | | |
| JOC4503 | | | | | | | | |
| Logic Low Output Voltage | 6N135 | V_{OL} | - | 0.18 | 0.4 | V | | |
| | 6N136 | | - | 0.25 | 0.4 | | | $I_F = 16\text{mA}$, $I_O = 3\text{mA}$, $V_{CC}=4.5\text{V}$, $T_a=25^\circ\text{C}$ |
| | JOC4502 | | | | | | | |
| | JOC4503 | | | | | | | |
| | 6N135 | | - | - | 0.5 | | | $I_F = 16\text{mA}$, $I_O = 0.8\text{mA}$, $V_{CC}=4.5\text{V}$ |
| 6N136 | - | - | 0.5 | $I_F = 16\text{mA}$, $I_O = 2.4\text{mA}$, $V_{CC}=4.5\text{V}$ | | | | |
| JOC4502 | | | | | | | | |
| JOC4503 | | | | | | | | |
| Isolation Resistance | Riso | 10^{12} | 10^{14} | - | Ω | DC500V, 40 ~ 60% R.H. | | |
| Floating Capacitance | C_{IO} | - | 0.3 | 1 | pF | V=0, f=1MHz | | |

ELECTRICAL OPTICAL CHARACTERISTICS

| PARAMETER | SYMBOL | MIN | TYP | MAX | UNIT | TEST CONDITION | NOTE | |
|---|-----------------------------|-----------------|-------|-------|------|----------------|--|--------|
| SWITCHING CHARACTERISTICS(at Ta=0 to 70°C, I _F =16mA, V _{CC} =5V, unless specified otherwise) | | | | | | | | |
| Propagation Delay Time to Logic Low | 6N135 | TPHL | - | 0.35 | 1.5 | μs | R _L =4.1kΩ, T _A =25°C | Fig.13 |
| | | | - | - | 2 | | R _L =4.1kΩ | |
| | 6N136 JOC4502 JOC4503 | | - | 0.35 | 0.8 | | R _L =1.9kΩ, T _A =25°C | |
| | | | - | - | 1.0 | | R _L =1.9kΩ | |
| Propagation Delay Time to Logic High | 6N135 | TPLH | - | 0.5 | 1.5 | μs | R _L =4.1kΩ, T _A =25°C | Fig.13 |
| | | | - | - | 2 | | R _L =4.1kΩ | |
| | 6N136 JOC4502 JOC4503 | | - | 0.3 | 0.8 | | R _L =1.9kΩ, T _A =25°C | |
| | | | - | - | 1.0 | | R _L =1.9kΩ | |
| Common Mode Transient Immunity at Logic High | 6N135 | CM _H | 1000 | - | - | V/μs | I _F = 0mA, V _{CM} =10Vpp, R _L =4.1kΩ, T _A =25°C | Fig.14 |
| | 6N136 JOC4502 | | 1000 | - | - | | I _F = 0mA, V _{CM} =10Vpp, R _L =1.9kΩ, T _A =25°C | |
| | JOC4503 | | 15000 | 20000 | - | | I _F = 0mA, V _{CM} =1500Vpp, R _L =1.9kΩ, T _A =25°C | |
| Common Mode Transient Immunity at Logic Low | 6N135 | CM _L | 1000 | - | - | V/μs | I _F = 16mA, V _{CM} =10Vpp, R _L =4.1kΩ, T _A =25°C | Fig.14 |
| | 6N136 JOC4502 | | 1000 | - | - | | I _F = 16mA, V _{CM} =10Vpp, R _L =1.9kΩ, T _A =25°C | |
| | JOC4503 | | 15000 | 20000 | - | | I _F = 16mA, V _{CM} =1500Vpp, R _L =1.9kΩ, T _A =25°C | |

CHARACTERISTIC CURVES

Fig.1 Forward Current vs. Forward Voltage




Fig.2 Forward Voltage vs. Ambient Temperature




Fig.3 Input Threshold Current vs. Ambient Temperature




Fig.4 Input Threshold Current vs. Ambient Temperature




Fig.5 Low Level Output Current vs. Ambient Temperature





Fig.6 Low Level Output Current vs. Ambient Temperature



CHARACTERISTIC CURVES

Fig.7 Low Level Output Voltage vs. Ambient Temperature




Fig.8 Low Level Output Voltage vs. Ambient Temperature




Fig.9 High Level Output Current vs. Ambient Temperature




Fig.10 High Level Output Current vs. Ambient Temperature




Fig.11 Output Voltage vs. Forward Current





Fig.12 Output Voltage vs. Forward Current



TEST CIRCUITS

Fig.13 Test Circuits for TPHL, TPLH, tr, tf





Fig.14 Waveforms of TPHL, TPLH, tr, tf



TEST CIRCUITS

Fig.15 Test Circuits for Common Mode Transient Immunity






Fig.16 Waveforms of Common Mode Transient Immunity




PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Standard DIP – Through Hole (DIP Type)




Gullwing (400mil) Lead Forming – Through Hole (M Type)




PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming (S Type)




Surface Mount (Low Profile) Lead Forming (SL Type)




PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Surface Mount (Gullwing) Lead Forming (SLM Type)




Recommended Solder Mask (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming & Surface Mount (Low Profile) Lead Forming




Surface Mount (Gullwing) Lead Forming




Carrier Tape Specifications (Dimensions in mm unless otherwise stated)

Option S(T1) & SL(T1)




Option S(T2) & SL(T2)




Carrier Tape Specifications (Dimensions in mm unless otherwise stated)

Option SLM(T1)




Option SLM(T2)



ORDERING AND MARKING INFORMATION

MARKING INFORMATION



JOC : Company Abbr.
 6N13X : Part Number
 VYAWW : LOT NO.

ORDERING INFORMATION

6N13X(Y)(Z)-GV

6N13X – Part Number (X=5 or 6)
 Y – Lead Form Option
 (M/S/SL/SLM/None)
 Z – Tape and Reel Option (T1/T2)
 G – Material Option
 (G: Green, None: Non-Green)
 V – VDE Option (V or None)

LABEL INFORMATION

 捷捷微电（深圳）有限公司
 JIEJIE MICROELECTRONICS (Shenzhen) Co Ltd

Part No.:XXXXXXXXXX Bin Code: X



Lot No.:XXXXXXXXXX

Date Code: XXXX

QTY: XXX PCS




PACKING QUANTITY

| Option | Quantity | Quantity – Inner box | Quantity – Outer box |
|--------|-----------------|----------------------|------------------------------------|
| None | 40 Units/Tube | 30 Tubes/Inner box | 10 Inner box/Outer box = 12k Units |
| M | 40 Units/Tube | 30 Tubes/Inner box | 10 Inner box/Outer box = 12k Units |
| S(T1) | 1000 Units/Reel | 3 Reels/Inner box | 5 Inner box/Outer box = 15k Units |
| S(T2) | 1000 Units/Reel | 3 Reels/Inner box | 5 Inner box/Outer box = 15k Units |
| SL(T1) | 1000 Units/Reel | 3 Reels/Inner box | 5 Inner box/Outer box = 15k Units |
| SL(T2) | 1000 Units/Reel | 3 Reels/Inner box | 5 Inner box/Outer box = 15k Units |

ORDERING AND MARKING INFORMATION

MARKING INFORMATION



JOC : Company Abbr.
450X : Part Number & Rank
V : VDE Option
Y : Fiscal Year
A : Manufacturing Code
WW : Work Week

ORDERING INFORMATION

JOC450X(Y)(Z)-GV

JOC – Company Abbr.
 450X – Rank (X=2 or 3)
 Y – Lead Form Option
 (M/S/SL/SLM/None)
 Z – Tape and Reel Option (T1/T2)
 G – Material Option
 (G: Green, None: Non-Green)
 V – VDE Option (V or None)

LABEL INFORMATION

 捷捷微电（深圳）有限公司
 JIEJIE MICROELECTRONICS (Shenzhen) Co Ltd

Part No.:XXXXXXXXXX Bin Code: X


 Lot No.: XXXXXXXXXXXX
 Date Code: XXXX
 QTY: XXX PCS
  

PACKING QUANTITY

| Option | Quantity | | |
|--------|----------|--|--|
| None | | | |
| M | | | |
| S(T1) | | | |
| S(T2) | | | |
| SL(T1) | | | |
| SL(T2) | | | |

REFLOW INFORMATION

REFLOW PROFILE



| Profile Feature | Sn-Pb Assembly Profile | Pb-Free Assembly Profile |
|--|------------------------|--------------------------|
| Temperature Min. (T_{smin}) | 100 | 150°C |
| Temperature Max. (T_{smax}) | 150 | 200°C |
| Time (t_s) from (T_{smin} to T_{smax}) | 60-120 seconds | 60-120 seconds |
| Ramp-up Rate (t_L to t_P) | 3°C/second max. | 3°C/second max. |
| Liquidous Temperature (T_L) | 183°C | 217°C |
| Time (t_L) Maintained Above (T_L) | 60 – 150 seconds | 60 – 150 seconds |
| Peak Body Package Temperature | 235°C +0°C / -5°C | 260°C +0°C / -5°C |
| Time (t_P) within 5°C of 260°C | 20 seconds | 30 seconds |
| Ramp-down Rate (T_P to T_L) | 6°C/second max | 6°C/second max |
| Time 25°C to Peak Temperature | 6 minutes max. | 8 minutes max. |

DISCLAIMER

- JIEJIE is continually improving the quality, reliability, function and design. JIEJIE reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- JIEJIE makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, JIEJIE disclaims (a) any and all liability arising out of the application or use of any product, (b) any and all liability, including without limitation special, consequential or incidental damages, and (c) any and all implied warranties, including warranties of fitness for particular
- The products shown in this publication are designed for the general use in electronic applications such as office automation, equipment, communications devices, audio/visual equipment, electrical application and instrumentation purpose, non-infringement and merchantability.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Please contact JIEJIE sales agent for special application request.
- Immerge unit's body in solder paste is not recommended.
- Parameters provided in datasheets may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated in each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify JIEJIE's terms and conditions of purchase, including but not limited to the warranty expressed therein.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.